

10/523,322

1-30. (CANCELED)

31. (CURRENTLY AMENDED) An interlacing device (10, 10') for a palletizing machine (1) which palletizes elongated products (2) that are ~~designed~~ to be deposited in superimposed rows on at least one transport pallet (7), the interlacing device (10, 10') comprising:

at least one interlacing gantry (11, 11') extending generally parallel to and along at least a portion of a length of the products (2) and the at least one interlacing gantry (11, 11') comprising[[:]]:

at least two upright posts joined at the top by a cross-beam, the interlacing gantry (11, 11') further comprising;

at least one guide (20, 20') supplied by at least one spool (12) of an interlacing material (12'); [[and]]

wherein the interlacing device (10, 10') also comprises drive means which is operated independently of ~~from the~~ operation of the palletizing machine (1) which palletizes the elongated products (2), the drive means ~~being~~ is connected to the interlacing gantry (11, 11') for displacing the interlacing gantry (11, 11') within the palletizing machine (1) and relative to a base structure of the interlacing device (10, 10'), between at least two alternate end positions so as to displace alternately the guide (20, 20') in at least one interlacing plane (P) that is essentially perpendicular to the palletized products (2) ~~alternately~~ from one side to another side of the transport pallet (7).

32. (CURRENTLY AMENDED) The interlacing device according to claim 31, wherein the drive means causes the interlacing gantry (11, 11') to pivot alternately at least once ~~one time~~.

33. (CURRENTLY AMENDED) The interlacing device according to claim 31, wherein the drive means (14) causes the interlacing gantry (11, 11') to move at least once in alternate translation ~~at least one time~~.

34. (CURRENTLY AMENDED) The interlacing device according to claim 31, wherein the drive means (14) [[are]] is selected from the group comprising at least electric motors (15), hydraulic cylinders and pneumatic cylinders.

0007-323 PM

- 3 -

10/523,322

35. (CURRENTLY AMENDED) The interlacing device according to claim 34, wherein the drive means (14) comprise at least one transmission system selected from the group comprising at least pinions and a chain (16), and a pulley and a belt. ♦♦

36. (CURRENTLY AMENDED) The interlacing device according to claim 33 further comprising at least one chassis (19) equipped with guide means for moving the interlacing gantry (11, 11') translationally in a translational direction. ♦♦

37. (PREVIOUSLY PRESENTED) The interlacing device according to claim 36, wherein the guide means comprises at least one pathway (18) formed in the chassis (19) to receive rollers (17) integral with vertical posts (11a) on the interlacing gantry (11, 11').

38. (PREVIOUSLY PRESENTED) The interlacing device according to claim 31, wherein the interlacing gantry (11, 11') comprises at least two guides (20, 20') located on the interlacing gantry (11, 11') to distribute at least two interlacing ties (12') in at least two essentially parallel interlacing planes (P) distributed along the palletized products (2).

39. (PREVIOUSLY PRESENTED) The interlacing gantry according to claim 38, wherein at least one of the two guides (20') is associated with activating means (21) which displace the at least one of the two guides (20') in alternate translation along the interlacing gantry (11') for a predetermined distance (D) to displace the interlacing plane (P) essentially parallel to itself.

40. (CURRENTLY AMENDED) The interlacing device according to claim 39, wherein the activating means (21) ~~[[are]]~~ is selected from the group comprising at least electric motors, hydraulic cylinders and pneumatic cylinders. ♦♦

41. (CURRENTLY AMENDED) A palletizing machine (1) for elongated cylindrical products (2), the palletizing machine (1) comprising: ♦♦

at least one gantry (3), one ~~movable~~ carrier (4) being movable in vertical translation along the gantry (3), at least one ~~movable~~ gripping device (5) being movable in horizontal translation on the carrier (4) and ~~designed~~ to remove the products (2) from a storage ramp (6) and deposit ~~[[them]]~~ the products (2) on a transport pallet (7); ♦♦

0000 0000 0000

10/523,322

at least one interlacing device (10, 10') being separate from the palletizing machine (1) and comprising at least one interlacing gantry (11, 11') extending generally parallel to and along at least a portion of a length of the products (2), the interlacing gantry (11, 11') comprising at least one guide (20, 20') supplied by at least one spool (12) of an interlacing material (12'); [[and]]

wherein the interlacing device (10, 10') also comprises drive means separate from the operation of the palletizing machine (1) which palletizes the elongated cylindrical products (2), the drive means being connected to the interlacing gantry (11, 11') for displacing the interlacing gantry (11, 11') inside the palletizing machine (1), vertically below the gripping device (5), and relative to a base structure of the interlacing device (10, 10'), and between at least two alternate end positions so as to displace the guide (20, 20') in at least one interlacing plane (P) that is essentially perpendicular to the palletized products (2) alternately from one side to another side of the transport pallet (7).

42. (CURRENTLY AMENDED) The palletizing machine according to claim 41, wherein the at least one interlacing gantry (11, 11') has dimensions that permit the interlacing device (10, 10') to be integrated located within the gantry (3) of the palletizing machine (1) below the gripping device (5) and outside the transport pallet (7) and the palletized products (2).

43. (PREVIOUSLY PRESENTED) The palletizing machine according to claim 41, wherein the gripping device (5') comprises means for controlling a drive means associated with the drive means for the palletizing machine (1) in order to displace the interlacing gantry (11, 11') alternately from one side of the transport pallet (7) to the other essentially parallel to the interlacing planes as the palletizing of the products (2) deposited on the transport pallet (7) progresses and according to a predetermined interlacing pattern.

44. (PREVIOUSLY PRESENTED) The palletizing machine according to claim 41, wherein at least one of the guides (20') on the interlacing device (10') is associated with activating means (21) designed to displace the at least one of the

08/07/2007 10:50 AM

10/523,322

guides (20') in alternate translation along the interlacing gantry (11') for a predetermined distance (D) so as to displace the corresponding interlacing plane (P) essentially parallel to itself.

45. (PREVIOUSLY PRESENTED) The palletizing machine according to claim 43, wherein the control means are designed to control the means (21) for activating the guide (20') so as to wrap the interlacing material (12') around posts (7') on the transport pallet (7) as palletization of the products (2) progresses and in a predetermined interlacing pattern.

46. (CURRENTLY AMENDED) An interlacing device (10, 10') for interlacing a tie material between palletized products deposited by a palletizing machine, the interlacing device comprising:

an interlacing gantry (11, 11') extending generally parallel to and along at least a portion of a length of the palletized products (2), the interlacing gantry (11, 11') having at least one guide (20, 20') supplied by at least one spool (12) of the tie material for facilitating the interlacing of the tie material between the palletized products; and

a drive for displacing the interlacing gantry (11, 11') between a first position and a second position and laying the tie material along at least one interlacing plane (P) so as to separate portions of the palletized products from one another; [[and]]

wherein the drive for displacing the interlacing gantry (11, 11') is independent from any drive of the palletizing machine so that operation of the interlacing gantry does not interfere with operation of the palletizing machine, and the drive is coupled to the interlacing gantry (11, 11') for displacing the interlacing gantry (11, 11') inside the palletizing machine (1) and relative to a base structure of the interlacing device (10, 10').

47. (PREVIOUSLY PRESENTED) The interlacing device according to claim 46, wherein the interlacing gantry further comprises a pair of posts (11a) interconnected at a top end thereof by a cross-beam (11b) and supporting the at least one guide for guiding the tie material relative to the palletized products in alternating translation.

08/03/2007 10:50 PM

10/523,322

48. (PREVIOUSLY PRESENTED) The interlacing device according to claim 47, wherein the interlacing device further comprises at least one chassis (19) equipped with a pathway for guiding the pair of posts (11a) interconnected by the cross-beam (11b) to move relative to the palletized products in alternating translation.

49. (PREVIOUSLY PRESENTED) The interlacing device according to claim 48, wherein the pathway (18) for guiding the pair of posts (11a) is formed in the chassis (19) to receive rollers (17) supporting the pair of posts (11a).

50. (PREVIOUSLY PRESENTED) The interlacing device according to claim 46, wherein the at least one guide for guiding the tie material relative to the palletized products in alternating translation in a first direction further comprises an actuator means (21) for moving the guide relative to the interlacing gantry in alternating translation in a second direction substantially perpendicular to the first direction to wrap the interlacing material around a post supporting the palletized products.

2007-0220 PM